

**WILCO PROJECT - 2008 REVERSE CIRCULATION DRILL PROGRAM(WR-049 to WR-087)**

Drillhole	Target Area	Au oz/ton	Drillhole interval feet	From feet	To feet	TD (feet)	Au g/tonne	Drillhole interval metres	From metres	To metres	TD (metres)
WR-049	Section Line	0.054	20	285	305	815	1.85	6.1	86.9	93.0	248.4
WR-049	Section Line	0.030	90	325	415		1.03	27.4	99.1	126.5	
WR-049	Section Line	0.031	80	590	670		1.06	24.4	179.8	204.2	
WR-050	Section Line	0.075	30	265	295	900	2.57	9.1	80.8	89.9	274.3
Including		0.183	10	265	275		6.28	3.0	80.8	83.8	
WR-050	Section Line	0.023	10	655	665		0.79	3.0	199.6	202.7	
WR-051	Section Line	NSV				785	NSV				239.3
WR-052	Section Line	0.019	20	390	410	515	0.65	6.1	118.9	125.0	157.0
WR-052	Section Line	0.018	20	445	465		0.62	6.1	135.6	141.7	
WR-053	Section Line	0.010	15	350	365	965	0.34	4.6	106.7	111.3	294.1
WR-053	Section Line	0.068	75	390	465		2.33	22.9	118.9	141.7	
WR-053	Section Line	0.010	10	520	530		0.34	3.0	158.5	161.5	
WR-053	Section Line	0.012	40	555	595		0.41	12.2	169.2	181.4	
WR-053	Section Line	0.013	35	610	645		0.45	10.7	185.9	196.6	
WR-053	Section Line	0.010	10	690	700		0.34	3.0	210.3	213.4	
WR-053	Section Line	0.028	65	725	790		0.96	19.8	221.0	240.8	
WR-054	Section Line	0.038	35	265	300	765	1.30	10.7	80.8	91.4	233.2
WR-054	Section Line	0.010	20	350	370		0.34	6.1	106.7	112.8	
WR-054	Section Line	0.029	130	440	570		0.99	39.6	134.1	173.7	
Including		0.118	5	480	485		4.05	1.5	146.3	147.8	
WR-055	Section Line	NSV				730	NSV				222.5
WR-056	Section Line	NSV				725	NSV				221.0
WR-057	Section Line	0.014	10	260	270	645	0.48	3.0	79.2	82.3	196.6
WR-057	Section Line	0.012	25	310	335		0.41	7.6	94.5	102.1	
WR-057	Section Line	0.025	65	385	450		0.86	19.8	117.3	137.2	
WR-057	Section Line	0.014	20	540	560		0.48	6.1	164.6	170.7	
WR-057	Section Line	0.016	10	625	635		0.55	3.0	190.5	193.5	
WR-058	Section Line	0.012	10	290	300	700	0.41	3.0	88.4	91.4	213.4
WR-058	Section Line	0.014	10	390	400		0.48	3.0	118.9	121.9	
WR-058	Section Line	0.039	150	480	630		1.34	45.7	146.3	192.0	
Including		0.126	10	515	525		4.32	3.0	157.0	160.0	
Including		0.103	5	535	540		3.53	1.5	163.1	164.6	
WR-059	Section Line	0.068	55	165	220	800	2.33	16.8	50.3	67.1	243.8
Including		0.291	10	165	175		9.98	3.0	50.3	53.3	
WR-059	Section Line	0.051	10	320	330		1.75	3.0	97.5	100.6	
Including		0.100	5	325	330		3.43	1.5	99.1	100.6	
WR-059	Section Line	0.024	25	675	700	1215	0.82	7.6	205.7	213.4	370.3
WR-060	Section Line	0.013	25	545	570		0.45	7.6	166.1	173.7	
WR-060	Section Line	0.020	20	585	605	1055	0.69	6.1	178.3	184.4	321.6
WR-061	Section Line	0.036	10	530	540		1.23	3.0	161.5	164.6	
WR-061	Section Line	0.011	20	840	860		0.38	6.1	256.0	262.1	
WR-061	Section Line	0.039	60	890	950		1.34	18.3	271.3	289.6	
WR-061	Section Line	0.043	25	960	985		1.47	7.6	292.6	300.2	
Including		0.138	5	970	975	4.73	1.5	295.7	297.2		
WR-062	Section Line	0.010	10	355	365	1025	0.34	3.0	108.2	111.3	312.4
WR-062	Section Line	0.016	30	740	770		0.55	9.1	225.6	234.7	
WR-062	Section Line	0.100	10	790	800		3.43	3.0	240.8	243.8	
WR-062	Section Line	0.041	50	855	905		1.41	15.2	260.6	275.8	
WR-063	Pay-Dirt	0.014	15	35	50	935	0.48	4.6	10.7	15.2	285.0
WR-063	Pay-Dirt	0.013	10	120	130		0.45	3.0	36.6	39.6	
WR-063	Pay-Dirt	0.011	10	175	185		0.38	3.0	53.3	56.4	

**WILCO PROJECT - 2008 REVERSE CIRCULATION DRILL PROGRAM(WR-049 to WR-087)**

Drillhole	Target Area	Au oz/ton	Drillhole interval feet	From feet	To feet	TD (feet)	Au g/tonne	Drillhole interval metres	From metres	To metres	TD (metres)
WR-064	Pay-Dirt	0.015	20	80	100	300	0.51	6.1	24.4	30.5	91.4
WR-064	Pay-Dirt	0.010	10	130	140		0.34	3.0	39.6	42.7	
WR-064	Pay-Dirt	0.010	30	180	210		0.34	9.1	54.9	64.0	
WR-065	Section Line	0.015	20	210	230	945	0.51	6.1	64.0	70.1	288.0
WR-065	Section Line	0.015	10	440	450		0.51	3.0	134.1	137.2	
WR-066	Section Line	0.020	25	420	445	955	0.69	7.6	128.0	135.6	291.1
WR-067	Section Line	0.013	10	260	270	905	0.45	3.0	79.2	82.3	275.8
WR-067	Section Line	0.011	10	420	430		0.38	3.0	128.0	131.1	
WR-068	Section Line	0.038	50	255	305	625	1.30	15.2	77.7	93.0	190.5
WR-068	Section Line	0.014	15	430	445		0.48	4.6	131.1	135.6	
WR-069	Section Line	0.012	25	545	570	700	0.41	7.6	166.1	173.7	213.4
WR-070	Section Line	0.031	15	410	425	550	1.06	4.6	125.0	129.5	167.6
WR-070	Section Line	0.037	15	445	460		1.27	4.6	135.6	140.2	
WR-071	Section Line	0.011	10	290	300	550	0.38	3.0	88.4	91.4	167.6
WR-072	Section Line	0.011	10	505	515	700	0.38	3.0	153.9	157.0	213.4
WR-072	Section Line	0.017	30	540	570		0.58	9.1	164.6	173.7	
WR-073	Section Line	0.030	10	445	455	835	1.03	3.0	135.6	138.7	254.5
WR-073	Section Line	0.044	70	515	585		1.51	21.3	157.0	178.3	
WR-074	Section Line	0.010	20	410	430	665	0.34	6.1	125.0	131.1	202.7
WR-074	Section Line	0.057	55	450	505		1.95	16.8	137.2	153.9	
WR-075	Section Line	0.012	10	585	595	665	0.41	3.0	178.3	181.4	202.7
WR-076	Section Line	0.016	15	670	685	835	0.55	4.6	204.2	208.8	254.5
WR-076	Section Line	0.011	10	755	765		0.38	3.0	230.1	233.2	
WR-076	Section Line	0.021	10	785	795		0.72	3.0	239.3	242.3	
WR-077	Section Line	0.010	30	215	245	950	0.34	9.1	65.5	74.7	289.6
WR-077	Section Line	0.024	10	410	420		0.82	3.0	125.0	128.0	
WR-077	Section Line	0.061	15	485	500		2.09	4.6	147.8	152.4	
WR-077	Section Line	0.021	10	810	820		0.72	3.0	246.9	249.9	
WR-077	Section Line	0.066	15	890	905		2.26	4.6	271.3	275.8	
WR-078	Section Line	0.015	35	605	640	1265	0.51	10.7	184.4	195.1	385.6
WR-078	Section Line	0.058	10	1095	1105		1.99	3.0	333.8	336.8	
	Including	0.113	5	1100	1105		3.87	1.5	335.3	336.8	
WR-078	Section Line	0.012	10	1180	1190		0.41	3.0	359.7	362.7	
WR-079	Section Line	0.022	45	570	615	1065	0.75	13.7	173.7	187.5	324.6
WR-079	Section Line	0.015	25	770	795		0.51	7.6	234.7	242.3	
WR-079	Section Line	0.018	20	820	840		0.62	6.1	249.9	256.0	
WR-079	Section Line	0.034	40	855	895		1.17	12.2	260.6	272.8	
WR-079	Section Line	0.028	40	905	945		0.96	12.2	275.8	288.0	
WR-080	Section Line	0.012	20	625	645	1075	0.41	6.1	190.5	196.6	327.7
WR-080	Section Line	0.020	45	670	715		0.69	13.7	204.2	217.9	
WR-080	Section Line	0.010	10	730	740		0.34	3.0	222.5	225.6	
WR-080	Section Line	0.018	10	790	800		0.62	3.0	240.8	243.8	
WR-080	Section Line	0.034	10	845	855		1.17	3.0	257.6	260.6	
WR-080	Section Line	0.010	10	890	900		0.34	3.0	271.3	274.3	
WR-080	Section Line	0.012	10	1025	1035		0.41	3.0	312.4	315.5	
WR-081	North Basin	0.016	15	460	475	1265	0.55	4.6	140.2	144.8	385.6
WR-081	North basin	0.011	10	540	550		0.38	3.0	164.6	167.6	
WR-081	North Basin	0.015	10	905	915		0.51	3.0	275.8	278.9	
WR-081	North Basin	0.053	10	1105	1115		1.82	3.0	336.8	339.9	
	Including	0.102	5	1100	1105		3.50	1.5	335.3	336.8	
WR-081	North Basin	0.057	120	1120	1240			1.95	36.6	341.4	

**WILCO PROJECT - 2008 REVERSE CIRCULATION DRILL PROGRAM(WR-049 to WR-087)**

Drillhole	Target Area	Au oz/ton	Drillhole interval feet	From feet	To feet	TD (feet)	Au g/tonne	Drillhole interval metres	From metres	To metres	TD (metres)
	Including	0.140	10	1160	1170		4.80	3.0	353.6	356.6	
	Including	0.107	30	1180	1210		3.67	9.1	359.7	368.8	
WR-081	North Basin	0.011	10	1255	1265		0.38	3.0	382.5	385.6	
WR-082	Colado Resource	0.016	40	90	130		0.55	12.2	27.4	39.6	
WR-082	Colado Resource	0.079	35	190	225		2.71	10.7	57.9	68.6	
	Including	0.161	10	205	215		5.52	3.0	62.5	65.5	
WR-082	Colado Resource	0.011	15	235	250	1272	0.38	4.6	71.6	76.2	387.7
WR-082	Colado Resource	0.010	10	265	275		0.34	3.0	80.8	83.8	
WR-082	Colado Resource	0.017	15	330	345		0.58	4.6	100.6	105.2	
WR-082	Colado Resource	0.013	15	440	455		0.45	4.6	134.1	138.7	
WR-082	Colado Resource	0.012	10	515	525		0.41	3.0	157.0	160.0	
WR-082	Colado Resource	0.012	10	515	525		0.41	3.0	157.0	160.0	
WR-083	Area 46	0.012	15	230	245	535	0.41	4.6	70.1	74.7	163.1
WR-084	Area 46	NSV				600	NSV				182.9
WR-085	Old Willard Mine	NSV				500	NSV				152.4
WR-086	Old Willard Mine	NSV				680	NSV				207.3
WR-087	North Basin	0.011	25	275	300	1275	0.38	7.6	83.8	91.4	388.6
WR-087	North Basin	0.020	65	320	385		0.69	19.8	97.5	117.3	
WR-087	North Basin	0.082	15	450	465		2.81	4.6	137.2	141.7	
WR-087	North Basin	0.076	125	1150	1275		2.61	38.1	350.5	388.6	
	Including	0.416	15	1160	1175			14.26	4.6	353.6	

NSV = No Significant Values